



Model	UNIT	JMC-42C	JMC-55C	JMC-84C	JMC-100C	JMC-118C
Туре	-	Three piece				
		welded	welded	welded	welded	welded
Specification		IS: 3196				
		(Pt. 4) 2001				
Water Capacity +3% - 0%	Lts.	42	55	84	100	118
Hydrostatic Stretch	Kgf/Cm2	30	30	30	30	30
Test Pressure						
Pneumatic Leakage	Kgf/Cm2	10	10	10	10	10
Test Pressure						
Maximum Working	Kgf/Cm2	19.9	19.9	19.9	19.9	19.9
Pressure						
Gas Capacity	Kg.	50	65	100	120	140
Tare Weight (Approx.)	Kg.	40	50	65	72	82
Outer Diameter	mm.	368	368	368	368	368
Inner Diameter	mm.	356	356	356	356	356
Wall Thickness	mm.	6	6	6	6	6
Length Without	mm.	565	700	980	1150	1350
Valve & Cap (Approx.)						
Valve Conforms To	-	IS: 3224				
Scope of Supply: Empty Chlorine Cylinders fitted with valve, guard, certified by BIS and approved by CCF.						

Scope of Supply: Empty Chlorine Cylinders fitted with valve, guard, certified by BIS and approved by CCE.